



# RAMOLENE™ RESIN

## COPO 17

Copolymer Polypropylene

### TYPICAL APPLICATIONS:

Automotive applications, consumer applications and household goods.

### PRODUCT DESCRIPTION:

RAMOLENE™ COPO 17 resin is a high impact copolymer with a medium melt flow rate and excellent processing properties.

# TECHNICAL DATA SHEET

PROPERTY	VALUE	ASTM
Melt Index @ 230°C/2.16 kg	17 g/10 min	D-1238
Density	0.90 g/cm <sup>3</sup>	D-1505
Tensile Strength at Yield	3260 PSI	D-638
Flexural Modulus, 1% Secant 0.050	179000 PSI	D-709A
Flexural Modulus, 1% Secant 0.0	203000 PSI	D-709B
Notched Izod Impact Strength, @ 73°F	No Break	D-256A
Deflection Temperature at 66 PSI	203°F	D-648
Elongation at Yield	4 %	D-638

All tests were run under laboratory conditions, ASTM (where applicable) testing procedures. The data are intended as a general guide only and do not necessarily represent results that may be obtained elsewhere. The use of Ramtech's products must be guided by the user's own methods for selection of proper formulation. RAMTECH OVERSEAS, INC. disclaims any responsibility for misuse or misapplication of its products. Ramtech makes no warranty of merchantability and there is no warranty that goods supplied shall be fit for any particular purpose.