



Ramtech Overseas, Inc
5017 West Laurel Street, Tampa, FL 33607, USA

**No. 620
PIPE CLEANER CLEAR**



MADE IN U.S.A.

DESCRIPTION:

Ramolene™ Pipe Cleaner No. 620 is a special blend of solvents formulated to clean PVC, CPVC, ABS and Styrene Pipes & Fittings, all schedules, and all diameters, prior to applying cement. This Pipe Cleaner will effectively remove oils, dirt, grease, and other foreign matter from the surface of pipe and inside of fitting. It is very important the surface of pipes and inside of fittings is clean for a strong leak proof joint. This product is made in the U.S.A.

APPLICATION:

Ramolene™ Cleaner may be used on PVC, CPVC, ABS and Styrene. Use applicator supplied with can or suitable applicator 1/2 the size of pipe being joined or clean cloth.

Application temperature: - 10 °F to 120 °F
Storage temperature: - 10 °F to 110 °F





PROPERTIES AND SPECIFICATIONS:

Color Clear
Appearance Liquid
Shelf Life: Unlimited (Unopened can)

AVAILABILITY:

SIZE	PART NO	UNITS/CARTON	
1/4 Pint / 4 Fluid Oz / 118 ml	62004	24	Can with brush in cap
1/2 Pint / 8 Fluid Oz / 237 ml	62008	24	Can with brush in cap
1 Pint / 16 Fluid Oz / 474 ml	62016	12	Can with brush in cap
1 Quart / 32 Fluid Oz / 946 ml	62032	12	Can with brush in cap

 <p>Ramtech Overseas, Inc 5017 West Laurel Street, Tampa, FL 33607, USA</p>	<p>No. 620 PIPE CLEANER CLEAR</p>	 <p>MADE IN U.S.A.</p>
--	---	---

DIRECTION FOR USE:

Keep container closed when not in use

1. Apply Cleaner with applicator supplied with can or suitable applicator or clean cloth
2. Wipe off with Clean Dry cloth
3. Apply cement according to instruction on cement can
4. Cement should not be applied when Cleaner is wet

PRECAUTIONS:

EXTREMELY FLAMMABLE LIQUID, VAPOR MAY IRRITATE EYE OR SKIN, MAY CASUE FLASH FIRE, MAY BE HARMFUL OR FATAL IF SWALLOWED. DO NOT USE NEAR HEAT, SPARKS, AND FLAMES. KEEP OUT OF REACH OF CHILDREN

Ensure adequate ventilation to avoid vapor buildup which may cause flash fire. Vapor build up may also cause dizziness, headache or eye watering. If symptoms are experienced use respiratory protection or leave area and provide more fresh air. Avoid contact with eyes, skin and clothing. Do not smoke and wear protective equipment while using

FIRST AID:

Inhalation: If breathing is difficult vacate to fresh air. If breathing problems persist seek immediate medical attention.

Eye Contact: Flush eyes thoroughly with water for 15 minutes. Seek immediate medical attention.

Ingestion: If swallowed, give 1-2 glasses of water or milk immediately, call physician, hospital, or poison control center immediately. DO NOT INDUCE VOMITING

SPILL: Remove all source of ignition and ventilate area. Soak up spill with absorbent material. Dispose of absorbent material in accordance with regulations. Personnel cleaning the spill should wear appropriate protective equipment.

WARRANTY: WARRANTY IS LIMITED TO REPLACEMENT OF DEFECTIVE MERCHANDISE